



公差/General Tolerances(mm)		公差/General Tolerances(mm)										公差/General Tolerances(mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	±2
3	6	10	18	30	50	80	120	180	250	315	400	500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

2	Pin	Copper	Sn Plated
1	Housing	LCP	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
UL 标准/UL Standard:		C	D
额定电压/Rated Voltage(V)/Current(A)		150/4	/
IEC 标准/IEC Standard:			/
过压类别/Overvoltage Category/污染等级		III/3	III/2
额定电压/电流/Rated Voltage(V)/Current(A)		/	250/5
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		/	2.5
间距/Pitch(mm)/线缆范围/Poles		2.5/N=02~12P	
使用温度范围/Operating Temperature(°C)		-40~+130	
符合RoHS环保要求/Conform to RoHS		Yes	

MATERIAL:	/	SURFACE:	/
MAT NO.:	/	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS:	/		
APPD:			
CHKD:			
DRFT:	Cen/MZ 2020.06.17	DRAWING NO.:	15EDGRC-THR-2.5-XXP-1Y-10A(H)
		TYPE:	CUSTOMER DRAWING

REV	ECN	DESCRIPTION	DRFT	DATE	SIZE: A4	SCALE: 2:1	SHEET 1/1